

5.12kWh

Rack Mounting Lithium Battery



HYBRID ENERGY STORAGE SYSTEM









Rack Mounting Lithium Battery

| LISTING DETAILS | | | MASTER BOX PACKAGING | | |
|----------------------------------|---------------|----------------------|----------------------|------------------|--|
| Model No: | VT48100E-P2 | | Qty Per Pallet: | 14pcs per pallet | |
| SKU Code: | 11377 | | Net Weight : | Approx. 41kg | |
| EAN Code: | 3800157689359 | | Product Size : | 445*400*130 mm | |
| GENERAL DA | TA | | | | |
| Nominal Capacity | | 100Ah@0.2C, 25°C | | | |
| Nominal Voltage | | 51.2V | | | |
| Nominal Energy | | 5.12kWh@0.2C, 25°C | | | |
| Charge Voltage | | 56.8V | | | |
| Standard Charge Current | | 20A@25°C | | | |
| Max Continuous Charge Current | | 100A@25 °C | | | |
| Standard Discharge Current | | 20A@25°C | | | |
| Max Continuous Discharge Current | | 100A@25 °C | | | |
| Discharge Cut-off Voltage | | 42.0V | | | |
| Operating Temperature | | Charge ∶ 0~+60°C | | | |
| | | Discharge ∶-20~+60°C | | | |
| Allowed Humidity Range | | ≤95% RH | | | |
| IP | | IP20 | | | |
| | | | | | |

TECHNICAL CURVES







LiFePO4 CATHODE MATERIAL



Self-designed BMS International design certification



LifePO4 cells, ensuring safety of the battery

6

Ş

Long cyclic life-6000 cycle (80% DOD)



High rate charge/discharge current @ 100A



Modular design Easy expandability